



The Proven Performer in Laundry



SPEED QUEEN® ON PREMISE LAUNDRY SOLUTIONS

Stacked Washer-Extractor/Tumble Dryers

SSA30

2×30 lb (14 kg)

SSA50

2×50 lb (23 kg)

- Offers all the benefits of a Speed Queen 30-pound washer-extractor and tumble dryer (50-pound version also available)
- A flush-mounted soap dispenser contributes to the machine's sleek, modern design, that includes stainless steel with chrome accents
- Minimal front fasteners gives quick access to key washer-extractor components to improve serviceability
- Reliability and durability that drastically outperforms retail or light commercial options
- Ideal for small OPL settings with limited space

Quantum® Touch Control

- Reimagine your laundry experience with the Speed Queen Quantum Touch display. Clear, easy to use, easy to understand directions with advanced cycle options and programs.
- User-friendly screens with operating instructions built in as part of the control
- 30+ languages available
- On-screen timer so you know exactly how much time your cycle will take



Stacked Washer-Extractor/Tumble Dryers

			SSA30		SSA50	
			Washer-Extractor	Tumble Dryer	Washer-Extractor	Tumble Dryer
Control Option			Quantum Touch		Quantum Touch	
Capacity - lb (kg)			30 (14) x 2		40 (18)	50 (23)
Overall Width - (mm)			(797)		(875)	
Overall Depth - (mm)			(1152)		(1302)	
Overall Height - (mm)			(2023)		(2141)	
Cylinder Diameter - (mm)			(610)	(762)	(668)	(838)
Cylinder Depth - (mm)			(406)	(660)	(515)	(762)
Cylinder Volume - (liters)			(119)	(300)	(178)	(419)
Reversing Cylinder			-	Standard	-	Standard
Door Opening Size - (mm)			(363)	(574)	(414)	(683)
Door Bottom to Floor - (mm)			(356)	(1303)	(370)	(1328)
Water Inlet Connection - (mm)			2 x (19)	-	2 x (19)	-
Drain Diameter - (mm)			1 x (76)	-	1 x (76)	-
Drain Height to Floor - (mm)			(108)	-	(115)	-
Heat Input Power - Btu/hr (kW, Mj/hr.)			-	73,000 (21.4, 77.0)	-	95,000 (27.8, 100)
Gas Connection - in			-	1/2 NPT	-	1/2 NPT
Air Outlet - (mm)			-	(200) Elliptical	-	(250) Elliptical
Airflow - cfm (l/sec)			-	400 (190)	-	600 (285)
Motor - HP (kW)	Fan		-	0.5 (0.4)	-	0.5 (0.4)
	Drive		1 (0.75)	0.3 (0.2)	2 (1.5)	0.5 (0.4)
Total # of Speeds			9	-	9	-
Cylinder Speeds - RPM (G-Force)	Gentle		34 (0.4)	-	33 (0.4)	-
	Wash		48 (0.8)	-	46 (0.8)	-
	Distribution		86 (2.5)	-	82 (2.5)	-
	Very Low		282 (27)	-	269 (27)	-
	Low		485 (80)	-	464 (80)	-
	Medium		542 (100)	-	518 (100)	-
	High		606 (125)	-	579 (125)	-
	Very High		664 (150)	-	635 (150)	-
	Ultra High		766 (200)	-	733 (200)	=
Electrical Specs - amps 200-240V/50/1/3			15	10	15	10
For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.						
Shipping Dimensions Approx. - (mm)	Width		(876)		(902)	
	Depth		(1194)		(1372)	
	Height		(2108)		(2261)	
Net Weight - (kg)			(349)		(413)	
Shipping Weight - (kg)			(357)		(422)	