Speed Queen
The Proven Performer in Laundry

Vended Hardmount Washer-Extractors

SC020, SC030, SC040, SC060, SC080

Features

- Rigid mounted, normal spin, 100G factor
- Stainless steel top and front panel
- Stainless steel drum and tub
- High capacity water inlets
- Large drain valve
- Large door opening for easy loading & unloading
- Industry-leading flexible water level settings
- Patented Fill and Drain leak detection saves water
- Lighter, computer-optimized frame
- Designed to reduce sound and vibration levels
- QuantumTM Gold Control
  - 27 Cycle – 8 Segment multi-level vend, time-of-day pricing, cycle modifier keys, 30 programmable water levels by segment & auto shut down. Dingle coin meter not included.

Options

- 200G factor (SC20-SC80)
- 165G factor (SC100)
- Stainless steel side panels
- Chrome door
- Steam heating version
- Electrical heating version

QuantumTM Gold Control

Robust Design

Large Drain Valve

Large Door Opening

Low Water Consumption

Vended Hardmount Washer-Extractors

Specifications

	SC020	SC030	SC040	SC060	SC080
Control Option	Gold	Gold	Gold	Gold	Gold
Capacity – [kg (lb)]	9 (20)	14 (30)	18 (40)	27 (60)	36 (80)
Overall Width – [mm (in)]	660 (26)	737 (29)	778 (30.6)	865 (34.1)	1054 (41.5)
Overall Depth – [mm (in)]	784 (30.9)	896 (35.3)	1073 (42.3)	1135 (44.7)	1196 (47.1)
Overall Height – [mm (in)]	1092 (43)	1143 (45)	1199 (47.2)	1267 (49.9)	1453 (57.2)
Cylinder Diameter – [mm (in)]	533 (21)	610 (24)	668 (26.3)	762 (30)	914 (36)
Cylinder Depth – [mm (in)]	350 (13.8)	406 (16)	515 (20.3)	559 (22)	556 (21.9)
Cylinder Volume – [l (cu. ft.)]	79.3 (2.8)	119 (4.2)	178 (6.3)	255 (9.0)	365 (12.9)
Door Opening Size – [mm (in)]	295 (11.6)	363 (14.3)	414 (16.3)	414 (16.3)	470 (18.5)
Door Bottom to Floor – [mm (in)]	365 (14.4)	356 (14)	370 (14.6)	379 (14.9)	455 (17.9)
Water Inlet Connection – [mm (in)]	2 @ 19 (0,75)	2 @ 19 (0,75)	2 @ 19 (0,75)	4 @ 19 (0,75)	4 @ 19 (0,75)
Drain Diameter – [mm (in)]	1 @ 76 (3)	1 @ 76 (3)	1 @ 76 (3)	1 @ 76 (3)	1 @ 76 (3)
Drain Height to Floor – [mm (in)]	99 (3,9)	109 (4,3)	114 (4,5)	124 (4,9)	130 (5,1)
Total # of Speeds	6,9	6,9	6,9	6,9	6,9
CYLINDER SPEEDS – [RPM (G-FORCE)]					
Gentle	37 (0.4)	34 (0.4)	33 (0.4)	31 (0.4)	28 (0.4)
Wash	51 (0.8)	48 (0.8)	46 (0.8)	43 (0.8)	39 (0.8)
Distribution	92 (2.5)	86 (2.5)	82 (2.5)	77 (2.5)	70 (2.5)
Very Low	301 (27)	282 (27)	269 (27)	252 (27)	230 (27)
Low	518 (80)	485 (80)	464 (80)	434 (80)	396 (80)
Medium	579 (100)	542 (100)	518 (100)	485 (100)	443 (100)
High	648 (125)	606 (125)	579 (125)	542 (125)	495 (120)
Very High	710 (150)	664 (150)	635 (150)	594 (150)	542 (150)
Ultra High	819 (200)	766 (200)	733 (200)	686 (200)	626 (200)
VOLTAGE WIRES/ CIRCUIT BREAKER – FLA					
120/60/1	15.IX	15.XII	20 – 15	N/A	N/A
200-208/220-240/50/60/3/1/3	15 – 4 (1 Ph) 15 – 3 (3 Ph)	15 – 7 (1 Ph) 15 – 4 (3 Ph)	15 – 7 (1 Ph) 15 – 4 (3 Ph)	15 – 11 (1 Ph) 15 – 7 (3 Ph)	20 – 15 (1 Ph) 15 – 9 (3 Ph)
200-208/220- 240/50/60/3/3	30 – 22	30 – 22	50 – 41	50 – 41	80-73
440–480/50/60/3/3	15 – 2	15 – 3	15 – 3	15 – 4	15 – 6
380–415/50/60/3/3	15 – 4	15 – 4	15 – 5	15 – 6	15 – 8
SHIPPING DIMENSIONS APPROX. - [mm (in)]					
Width	711 (28)	800 (31.5)	826 (32.5)	953 (37.5)	1118 (44)
Depth	859 (33.8)	973 (38.3)	1105 (43.5)	1191 (46.9)	1384 (54.5)
Height	1255 (49.4)	1303 (51.3)	1361 (53.6)	1430 (56.3)	1514 (59.6)
Motor Power Consumption – [kW (HP)]	0.75 (1)	0.75 (1)	1.5 (2)	2.2 (3)	3.7 (5)
Net Weight – [kg (lb)]	154 (340)	200 (440)	245 (540)	308 (680)	567 (1250)
Shipping Weight – [kg (lb)]	172 (380)	218 (480)	263 (580)	327 (720)	590 (1300)
Slat Crate Shipping Weight – [kg (lb)]	209 (460)	263 (580)	308 (680)	381 (840)	649 (1430)
Agency Approvals	cETLus, CE	cETLus, CE	cETLus, CE	cETLus, CE	cETLus, CE

Vended Hardmount Washer-Extractors

Dimensions

	Height	Width	Depth
SC020	1092	660	758
SC030	1143	737	897
SC040	1199	777	1074
SC060	1267	866	1135
SC080	1453	1054	1196
SC100	1453	1054	1298

All measurements in mm.



Speed Queen Laundry Systems
21 Hannigan Drive, Auckland 1072
Ph: +64 9 528 5600
Ph: 0800 77 333 7
W: www.speedqueen.co.nz
E: Sales@speedqueen.co.nz